


## PE 100 Stubb Suðufitting



Stubb Suðuflangs  
Stuttur

PE 100 Svart



Þvermál	Vörunúmer	Vörulýsing	SDR	s mm	L mm	L1 mm	Þyngd
450	25.012.6450.33	PE100 Suðuflangs ISO S-16	33	13,8	300	470	13.8
500	25.012.6500.33	PE100 Suðuflangs ISO S-16	33	15,3	300	475	14.2
560	25.012.6560.33	PE100 Suðuflangs ISO S-16	33	17,2	300	424	17.7
630	25.012.6630.33	PE100 Suðuflangs ISO S-16	33	19,3	300	480	20
450	25.012.6450.17	PE100 Suðuflangs ISO S-8	17	26,7	300	470	22.84
500	25.012.6500.17	PE100 Suðuflangs ISO S-8	17	29,7	300	470	24.48
560	25.012.6560.17	PE100 Suðuflangs ISO S-8	17	33,2	300	475	32.98
630	25.012.6630.17	PE100 Suðuflangs ISO S-8	17	37,4	300	480	36.5
710	25.012.6710.17	PE100 Suðuflangs ISO S-8	17	42,1	300	470	46.6
450	25.012.6450.11	PE100 Suðuflangs ISO S-5	11	40,9	300	466	31.8
500	25.012.6500.11	PE100 Suðuflangs ISO S-5	11	45,4	300	475	35
560	25.012.6560.11	PE100 Suðuflangs ISO S-5	11	50,8	300	480	47.3
630	25.012.6630.11	PE100 Suðuflangs ISO S-5	11	57,2	300	475	53
710	25.012.6710.11	PE100 Suðuflangs ISO S-5	11	64,5	300	470	68.7